

# Versilon™ TBOP Hose

## Unbraided Helically Convoluted Inner Tube Anti-Static Fluoropolymer Hose

Saint-Gobain Performance Plastics' Versilon TBOP hose is constructed with a black electrostatic dissipating conductive PTFE convoluted inner tube and has no braid reinforcement. The convoluted inner tube is extremely flexible and has open pitch helical convolutions to ensure smooth product flow.

Versilon TBOP hose's inner tube has a non-stick surface and cleans easily with steam, caustics, solvents or other cleaning agents.

### Features and Benefits

- Excellent chemical resistance
- Compatible with almost all materials
- Rounded, open-pitch helical convolutions shaped to ensure smooth product flow
- Non-stick surface, easy to clean (steam, caustics, solvents or other cleaning agents)
- Easy to flex, yet won't flatten when bent
- Can be clamped to sanitary tubing or pipe
- Cuff lengths can be varied to meet customer requirements
- Can be supplied with permanently attached Versilon fittings
- Extremely flexible
- Kink resistant

### Typical Applications

- Sanitary transfer
- Solvent transfer
- Drain and sample lines
- Semi-transparent sight gauges
- Ideal for drain lines

### Regulatory Compliance

- USDA
- US Pharmacopeia Class VI

## TBOP Hose Specifications

Part Number	Inside Diameter		Operating Pressure		Minimum Bend Radius		A Cuff I.D.		B Cuff O.D.		D Internal Diameter		E Convolution O.D.		C Standard Cuff Length	
	(in)	(mm)	(psi)	(MPa)	(in)	(mm)	(in)	(mm)	(in)	(mm)	(in)	(mm)	(in)	(mm)	(in)	(mm)
2804TBOP0	1/4	6.4	65	0.45	0.75	19.1	0.25	6.4	0.31	7.9	0.24	6.1	0.43	10.9	0.75	19.1
2806TBOP0	3/8	9.5	50	0.34	1.00	25.4	0.38	9.7	0.44	11.2	0.36	9.1	0.55	14.0	0.75	19.1
2808TBOP0	1/2	12.7	50	0.34	2.00	50.8	0.50	12.7	0.57	14.5	0.48	12.2	0.69	17.5	1.00	25.4
2812TBOP0	3/4	19.1	50	0.34	2.75	69.9	0.75	19.1	0.84	21.3	0.72	18.3	1.03	26.2	1.00	25.4
2816TBOP0	1	25.4	50	0.34	4.00	101.6	1.00	25.4	1.10	27.9	0.91	23.1	1.22	31.0	1.50	38.1
2824TBOP0	1-1/2	38.1	40	0.28	6.00	152.4	1.50	38.1	1.63	41.4	1.41	35.8	1.87	47.5	2.00	50.8
2832TBOP0	2	50.8	30	0.21	7.50	190.5	2.00	50.8	2.13	54.1	1.90	48.3	2.43	61.7	2.00	50.8
2840TBOP0	2-1/2	63.5	20	0.14	8.00	203.2	2.38	60.5	2.50	63.5	2.50	63.5	3.60	91.4	2.00	50.8
2848TBOP0	3	76.2	15	0.10	9.00	228.6	2.55	64.8	2.70	68.6	3.00	76.2	3.70	94.0	3.00	76.2
2864TBOP0	4	101.6	10	0.07	10.00	254.0	3.45	87.6	3.68	93.5	4.00	101.6	4.68	118.9	3.00	76.2

NOTE: Weights and outside diameter dimensions are nominal. Data given is for hose only. End fitting vs. hose pressure limitations must be considered and the lower of the two ratings must be used on assemblies. 2:1 burst/pressure rating.

### Construction

Inner Tube:	Black electrostatic dissipating conductive PTFE			
Reinforcement:	-			
Temperature Rating:	-100°F to +450°F -73°C to +232°C			
Maximum Length:	1/4" 3/8" 1/2" 3/4" 1"	100' 100' 100' 70' 65'	1-1/2" 2" 2-1/2" 3" 4"	70' 50' 30' 30' 20'

### Fitting Options

#### Versilon Crimp Style Fittings

- Over 40 styles of stocked crimp-style fittings in a wide range of materials
- Standard: 316L stainless steel (wetted surfaces)
- Flare-Thru fitting technology available for hose sizes 3/4" to 4":
  - 150 lb. lap-joint style flanged
  - Female cam and groove
  - Sanitary clamp style
  - 304 and 316 stainless steel flanges available

### Common Media

- General chemical transfer
- Caustic solutions

Limited Warranty: For a period of 6 months from the date of first sale, Saint-Gobain Performance Plastics Corporation warrants this product(s) to be free from defects in manufacturing. Our only obligation will be to provide replacement product for any portion proving defective, or at our option, to refund the purchase price thereof. User assumes all other risks, if any, including the risk of injury, loss or damage, whether direct or consequential, arising out of the use, misuse, or inability to use this product(s). SAINT-GOBAIN DISCLAIMS ANY AND ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.



Saint-Gobain Performance Plastics  
210 Harmony Road  
Mickleton, NJ 08056  
1-800-435-3992

www.processsystems.saint-gobain.com



NOTE: Saint-Gobain Performance Plastics Corporation does not assume any responsibility or liability for any advice furnished by it, or for the performance or results of any installation or use of the product(s) or of any final product into which the product(s) may be incorporated by the purchaser and/or user. The purchaser and/or user should perform its own tests to determine the suitability and fitness of the product(s) for the particular purpose desired in any given situation.

Versilon™ is a trademark of Saint-Gobain Performance Plastics.